

■業務用高性能グリスフィルター「ALフィルター」選定表 (1)両面型

番号	グリスフィルターチャンバー（ALフィルター取り付け枠）				ALフィルター「パンチングメタル有効開口85%」											
	型式	形状	寸法mm				フィルター型式	寸法mm			数量 枚	重量 kg	面風速 m/s	風量		圧力損失 Pa
			A	B	C	D		W	H	T				m ³ /min	m ³ /h	
1	AL-50V	<p>断面図</p>	507	694	485	470	AL-5050	500	500	25	2	5.4	1.1	28.0	1,680	33
2	AL-40V		507	580	403	388	AL-5040	500	400	25	2	4.2	1.1	22.4	1,344	33
3	AL-30V		507	466	321	306	AL-5030	500	300	25	2	3.4	1.1	16.8	1,008	33
4	AL-25V		507	408	280	265	AL-5025	500	250	25	2	2.6	1.1	14.0	840	33
5	AL-33V		307	466	315	306	AL-3030	300	300	25	2	2	1.1	10.0	600	33
6	AL-50V2	<p>断面図は両面型単体に準ずる。</p>	1,009	694	500	470	AL-5050	500	500	25	4	10.8	1.1	56.0	3,360	33
7	AL-40V2		1,009	580	418	388	AL-5040	500	400	25	4	8.4	1.1	44.8	2,680	33
8	AL-30V2		1,009	466	336	306	AL-5030	500	300	25	4	6.8	1.1	33.6	2,016	33
9	AL-25V2		1,009	408	295	265	AL-5025	500	250	25	4	5.2	1.1	28.0	1,680	33
10	AL-33V2		609	466	324	306	AL-3030	300	300	25	4	4	1.1	20.0	1,200	33
11	AL-50V3	<p>断面図は両面型単体に準ずる</p>	1,509	694	506	470	AL-5050	500	500	25	6	16.2	1.1	84.0	5,040	33
12	AL-40V3		1,509	580	424	388	AL-5040	500	400	25	6	12.6	1.1	67.2	4,032	33
13	AL-30V3		1,509	466	342	306	AL-5030	500	300	25	6	10.2	1.1	50.4	3,024	33
14	AL-25V3		1,509	408	301	265	AL-5025	500	250	25	6	7.8	1.1	42.0	2,528	33
15	AL-33V3		909	466	333	306	AL-3030	300	300	25	6	6	1.1	30.0	1,800	33

注記： 4連体・5連体の製作も可能です。

■業務用高性能グリスフィルター「ALフィルター」選定表 (2) 片面型

番号	グリスフィルターチャンバー（ALフィルター取り付け枠）				ALフィルター「パンチングメタル有効開口85」											
	型式	形状	寸法mm				フィルター型式	寸法mm			数量 枚	重量 kg	面風速 m/s	風量		圧力損失 Pa
			A	B	C	D		W	H	T				m ³ /min	m ³ /h	
1	AL-50H		507	417	485	470	AL-5050	500	500	25	1	2.7	1.1	14.0	840	33
2	AL-40H		507	360	403	388	AL-5040	500	400	25	1	2.1	1.1	11.2	672	33
3	AL-30H		507	303	321	306	AL-5030	500	300	25	1	1.7	1.1	8.4	504	33
4	AL-25H		507	274	280	265	AL-5025	500	250	25	1	1.3	1.1	7.0	402	33
5	AL-33H		307	303	315	306	AL-3030	300	300	25	1	1.0	1.1	5.0	300	33
6	AL-50H2		1,009	417	500	470	AL-5050	500	500	25	2	5.4	1.1	28.0	1,680	33
7	AL-40H2		1,009	360	418	388	AL-5040	500	400	25	2	4.2	1.1	22.4	1,344	33
8	AL-30H2		1,009	303	336	306	AL-5030	500	300	25	2	3.4	1.1	16.8	1,008	33
9	AL-25H2		1,009	274	295	265	AL-5025	500	250	25	2	2.6	1.1	14.0	840	33
10	AL-33H2		609	303	324	306	AL-3030	300	300	25	2	2.0	1.1	10.0	600	33
11	AL-50H3		1,509	417	506	470	AL-5050	500	500	25	3	8.1	1.1	42.0	2,528	33
12	AL-40H3		1,509	360	424	388	AL-5040	500	400	25	3	6.3	1.1	33.6	2,016	33
13	AL-30H3		1,509	303	342	306	AL-5030	500	300	25	3	5.1	1.1	25.2	1,512	33
14	AL-25H3		1,509	274	301	265	AL-5025	500	250	25	3	3.9	1.1	21.0	1,260	33
15	AL-33H3		909	303	333	306	AL-3030	300	300	25	3	3.0	1.1	15.0	900	33

注記： 4連体・5連体の製作も可能です。